



Product Information

ARTISAN®

Grease & Oil Remover

DESCRIPTION

Artisan completely lifts and absorbs oil stains from concrete, brick, pavers, asphalt and wood. No scrubbing is necessary. Simply apply Artisan over the stain, allow it to dry and sweep up dry residue.

Artisan is solvent and phosphate free. Artisan is blended with biodegradable ingredients. As it dries, Artisan will remove deep seated stains.

USES

Use Artisan on concrete, brick, pavers, asphalt and wood. Use to remove stains caused by oil, grease, anti freeze, transmission fluid, tar, wax, food stains, fire dressings, hydraulic fluid and other oil based materials.

PROPERTIES

Appearance	thick, opaque liquid
Odor	No added fragrances
Flash Point	N/A
lbs/gallon	9

FEATURES AND BENEFITS

- Water Based
- Biodegradable
- Does not contain any solvents such as glycol, alcohol or methanol.
- Non-flammable

COVERAGE

Approximately 60 square feet/gallon when using a 1/4" v-notched spreader.

APPLICATION

Apply directly on stain, extending approximately 1 inch past the edge of the stain. Allow to dry. Dry times vary depending on surface and air temperatures. Dry time can range from 2-6 hours.

After Artisan has completely dried, sweep up with powder and dispose of properly. Rinse surface with clean water to remove remaining residue.

PACKAGED

Artisan is available in gallons, 5 gallon pails and 55 gallon drums.

STORAGE AND SHELF LIFE

The shelf life is indefinite in closed containers. Keep from freezing.

DISPOSAL

Use completely or dispose of properly. Local requirements vary. Consult your local sanitation department or state designated environmental agency.



ARTISAN®
STONE CARE PRODUCTS





ARTISAN® Grease & Oil Remover

SAFETY AND HANDLING

For specific information, please refer to the material safety data sheet. Wear chemical resistant gloves, apron, footwear and goggles. Refer to product label and material safety data sheet for complete safety information.

Use only with adequate ventilation. Do not breathe spray mist. Ensure fresh air entry during application and drying. Avoid contact with eyes and prolonged or repeated contact with skin. Avoid exposure to mist by wearing a NIOSH approved respirator during application and clean up. Follow respirator manufacturer's directions for respirator use. Close container after each use. Wash thoroughly after handling. **FIRST AID:** In case of eye contact, flush with water for 15 minutes. Get immediate medical attention. In case of contact with skin, wash with soap and water. If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

IN CASE OF SPILL: Absorb with inert material and dispose of properly. **KEEP OUT OF REACH OF CHILDREN.** Refer to Material Safety Data Sheet available for further safety and handling information.

WARRANTY

Information and recommendations for this product are based on research performed by Chemique, Inc. and the research of others, and are believed to be accurate. However, no guarantee of the accuracy is made because we cannot cover every possible application of our products, or can we anticipate every variable that may be encountered regarding types masonry surfaces, job conditions, degradation, weathering, age and methods used. The purchaser and end user must make their own tests to determine the suitability of such products for each particular purpose.

Chemique, Inc. warrants this product to be free from defects. Chemique makes no other warranties with respect to this product, express or implied, including without limitation the implied warranties of merchantability or fitness for particular purpose. Chemique, Inc's liability shall be strictly limited to supplying sufficient product to re-clean the specific areas which defective product was applied. Acceptance and use of this product absolves Chemique, Inc. from any and all liability whatsoever, including liability for incidental, consequential or resultant damages whether due to breach of warranty, negligence or strict liability. This warranty may not be altered, modified or extended by representatives of Chemique, Inc., its distributors or dealers.

